

Product Datasheet

6-port Full Gigabit E Network Managed Industrial Ethernet Switch

(ONV-IPS53064FM)



OVERVIEW

The ONV-IPS53064FM is a full Gigabit e network managed industrial Ethernet fiber switch independently developed by ONV. It has 4*10/100/1000Base-T adaptive RJ45 ports and 2*1000Base-X uplink SFP fiber slot ports. Each port can support wire-speed forwarding.

ONV-IPS53064FM can support WEB management, as well as ONV-NMS management platform and mobile APP cloud platform management, which can realize functions such as security network topology management, link aggregation, port management, port mirroring and remote operation and maintenance. This switch has high reliability, easy installation and maintenance, fast switching function, and multiple access ports, which are suitable for access to LAN devices of various scales. The ONV-IPS53064FM industrial grade product fully follows the design and materials of industrial products. The shell is made of aluminum alloy to enhance heat dissipation, and has excellent adaptability to

industrial site environment (including mechanical stability, climate environment adaptability, electromagnetic environment adaptability, etc.), The protection level reaches IP40, supports dual redundant power supply, low-power no fan cooling technology, MTBF up to 35 years, and 5-year warranty. It is suitable for intelligent transportation, rail transportation, electric power industry, mining, petroleum, shipping, metallurgy and green energy construction and other industrial scenarios to build an economical, efficient, stable and reliable communication network.

FEATURE

■ Gigabit access, SFP fiber port uplink

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- ◇ Support Gigabit Ethernet port and Gigabit SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

■ Extreme optimization, minimalist application

- ◇ Real-time fault alarm and fault location.
- ◇ Remote upgrade, remote restart, and factory reset.
- ◇ Local platform, cloud platform and mobile APP operation and maintenance management.
- ◇ Visualized network topology management, VLAN division, QoS, link aggregation, ring network management, port mirroring, port control and bandwidth management.
- ◇ According to the application requirements of the industry, we have abandoned the complicated network management configuration while retaining the practical network management functions. Through the operation and maintenance platform, network deployment and centralized operation and maintenance can be quickly realized.

■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.
- ◇ Low power consumption, no fan design, aluminum shell.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR, SYS, Link, L/A.

TECHNICAL SPECIFICATION


| Model | ONV-IPS53064FM |
|----------------------------------|---|
| Interface Characteristics | |
| Fixed Port | 4*10/100/1000Base-T RJ45 ports (Data) 2*1000Base-X uplink SFP ports (Data) 2 groups of V+, V- redundant DC power port (5P phoenix terminal) |
| Ethernet Port | Port 1-4 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption |
| Twisted Pair Transmission | 10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter) |
| SFP Slot Port | Gigabit SFP optical fiber interface, default no included optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC) |
| Optical Cable/ Distance | Multi-mode: 850nm/ 0-500M, Single-mode: 1310nm/0-40KM, 1550nm / 0-120KM. |
| Chip Parameter | |
| Network Management Type | L2 (WEB management, platform management) |
| Network Protocol | IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3x |

| | |
|-------------------------------------|--|
| Forwarding Mode | Store and Forward(Full wire-speed) |
| Switching Capacity | 12Gbps |
| Forwarding Rate@64byte | 8.93Mpps |
| MAC | 2K |
| Buffer Memory | 2M |
| Jumbo Frame | 9.2K |
| LED Indicator | Power/System: SYS (Green), Network: Link (Yellow), Fiber port: L/A (Green) |
| Power Supply | |
| Total power/Input Voltage | 5W/12-57VDC |
| Power Consumption | Standby<4W, Full load<6W |
| Interface | 5 Pin industrial Phoenix terminal, support anti-reverse protection. |
| Power Supply | No, optional 48V/12W or 48V/24W industrial power supply |
| Physical Parameter | |
| Operation TEMP / Humidity | -40~+75°C, 5%~90% RH Non condensing |
| Storage TEMP / Humidity | -40~+85°C, 5%~95% RH Non condensing |
| Dimension (L*W*H) | 119*100*30mm |
| Net /Gross Weight | <0.35kg / <0.5kg |
| Installation | Desktop, 35mm DIN rail |
| Certification & Warranty | |
| Lightning Protection | Lightning protection: 6KV 8/20us; Protection level: IP40 IEC61000-4-2(ESD):±8kV contact discharge,±15kV air discharge IEC61000-4-3(RS):10V/m(80~1000MHz) |

| | |
|------------------------------------|--|
| | <p>IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV</p> <p>IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable:±4kV</p> <p>IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz)</p> <p>IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s</p> <p>IEC61000-4-9(pulsed magnet field):1000A/m</p> <p>IEC61000-4-10(damped oscillation):30A/m 1MHz</p> <p>IEC61000-4-12/18(Shockwave):CM 2.5kV,DM 1kV</p> <p>IEC61000-4-16(common-mode transmission):30V; 300V,1s</p> <p>FCC Part 15/CISPR22(EN55022):Class B</p> <p>IEC61000-6-2(Common Industrial Standard)</p> |
| Mechanical Properties | <p>IEC60068-2-6 (anti vibration)</p> <p>IEC60068-2-27 (anti shock)</p> <p>IEC60068-2-32 (free fall)</p> |
| Certification | CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS |
| Warranty | 5 years, lifelong maintenance. |
| Network Management Features | |
| Interface | <p>Port status display, Port traffic statistics</p> <p>Port duplex/negotiation rate configuration</p> <p>EEE Energy-saving and green Ethernet function</p> <p>IEEE802.3x flow control configuration (Full-duplex)</p> |
| VLAN | Port-based IEEE802.1Q VLAN configuration (4K) |
| Port Aggregation | Static aggregation |
| Loop Protection | Loop protection function |
| Multicast | IGMP Snooping v1/v2, Max 256 multicast groups |
| Port Mirroring | Bidirectional data mirroring based on port |
| QoS | <p>Diff-Serv QoS, Priority Mark/Remark</p> <p>8*Output queues of each port, 802.1p/DSCP priority mapping</p> |
| Security | Broadcast storm control, Port isolation, Port speed limit |

| | |
|------------|--|
| DHCP | DHCP Snooping |
| Management | Mobile APP operation and maintenance management ONV-NMS platform management (Local platform/Cloud platform) One-key recovery, Cable Diagnose, Web Management (HTTPS) |
| System | Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Category 5 and above Ethernet cables TCP/IP, network adapter, and network operating systems (Such as Microsoft Windows, Linux or Mac OS X) are installed on each computer in the network with Category 5 and above Ethernet cables |

DIMENSION



ORDERING INFORMATION

| Model | Description | Recommended Power Supply |
|----------------|---|--------------------------|
| ONV-IPS53064FM | E network managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 2*1000M SFP ports. Support DC redundant power input (Phoenix terminal connection) and DIN rail mounting. | 12W/24W |

Note: Industrial Ethernet switch does not included the SFP optical module and power supply.

PACKING LIST

| PACKING LIST | CONTENT | QTY | UNIT |
|--------------|---|-----|------|
| | 6-port full gigabit E network managed industrial switch | 1 | SET |
| | User Guide | 1 | PC |
| | Warranty Card | 1 | PC |

OPTICAL MODULE INFORMATION

| Product | Model | Description | Unit |
|----------------------|----------|--|------|
| 1.25G Optical Module | 2630-G | Industrial SFP optical module, 1.25G, multi-mode dual fiber 850nm, transmission distance: 550m, LC interface, support DDM function, support hot plug and pull. | PC |
| | 2632-G | Industrial SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull. | PC |
| | 2612-T-G | Industrial SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC | PC |

| | | | |
|-----------------|-------------|---|----|
| | | interface, support DDM function, support hot plug and pull. | |
| | 2613-R-G | Industrial SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull. | PC |
| | 2612-T-G-SC | Industrial SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull. | PC |
| | 2613-R-G-SC | Industrial SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull. | PC |
| Power Module | 2633 | 1.25G SFP optical module transfers to 10/100/1000M RJ45 port. | PC |

POWER SUPPLY

| Product | Model | Description | Unit |
|--|-------------|--|------|
| 12W DIN Rail Industrial Power Supply | GWS-DP12-12 | Din Rail type 12W single set of output power supply Input Voltage:AC 100V~240V 50-60H, 0.5A Output Voltage:DC 12V 1A Operation Temperature:-40℃—+70℃ | PC |
| 24W DIN Rail Industrial Power Supply | GWS-DP24-24 | Din Rail type 24W single set of output power supply Input Voltage:AC 100V~240V 50-60H,0.65A Output Voltage:DC 24V 1.0A Operation Temperature:-40℃—+70℃ | PC |

RELATED PRODUCT

| Model | Description |
|-----------------|--|
| ONV-IPS53054FM | E network managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 1*1000M SFP port. Support DC redundant power input and DIN rail mounting. |
| ONV-IPS53064FGM | E network managed industrial Ethernet fiber switch with 5*10/100/1000M RJ45 ports and 1*1000M SFP port. Support DC redundant power input and DIN rail mounting. |
| ONV-IPS53008FM | E network managed industrial Ethernet switch with 8*10/100/1000M RJ45 ports. Support DC redundant power input and DIN rail mounting. |
| ONV-IPS53108FM | E network managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 2*1000M SFP ports. Support DC redundant power input and DIN rail mounting. |

CONTACT US

ONV OPTICAL NETWORK VIDEO TECHNOLOGIES (SHENZHEN) CO., LTD.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

Website: www.onvcom.com

Email/Skype/WeChat ID: onv@onv.com.cn

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen, China

Factory Address: The 4-6th Floor, No. 59, Huaning Road, Xinwei Community, Dalang Street, Longhua District, Shenzhen, China.

