

## Product Datasheet

### 6-port Full Gigabit Cloud Managed Industrial Ethernet Switch (ONV-IPS53064FM)



## OVERVIEW

The ONV-IPS53064FM is a full Gigabit cloud managed industrial Ethernet fiber switch independently developed by ONV. It has 4\*10/100/1000Base-T adaptive RJ45 ports and 2\*100/1000Base-X uplink SFP fiber slot ports. Each port can support wire-speed forwarding.

The ONV-IPS53064FM can support Web management, ONV-NMS management platform and mobile APP cloud platform management, which can realize functions such as security network topology management, link aggregation, port management, port mirroring and remote operation and maintenance. The switch has high reliability, easy installation and maintenance, fast switching function, and multiple access ports, which are suitable for access to LAN devices of various scales. The ONV-IPS53064FM switch follows the design and materials of industrial products. The shell is made of aluminum alloy to enhance heat dissipation, and has excellent adaptability to industrial site environment, The protection level is IP40, supports dual redundant power supply, MTBF up to 35 years,

and 5 years warranty. It is suitable for intelligent transportation, rail transportation, electric power industry, mining, petroleum, shipping, metallurgy and green energy construction and other industrial scenarios to build an economical, efficient, stable and reliable communication network.

## FEATURE

### ■ Gigabit access, SFP fiber port uplink

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- ◇ Support Gigabit Ethernet port and Gigabit SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

### ■ Extreme optimization, minimalist application

- ◇ Real-time fault alarm and fault location.
- ◇ Remote upgrade, remote restart, and factory reset.
- ◇ Local platform, cloud platform and mobile APP operation and maintenance management.
- ◇ Visualized network topology management, VLAN division, QoS, link aggregation, ring network management, port mirroring, port control and bandwidth management.
- ◇ According to industry application requirements, complex network management configurations are discarded, practical network management functions are retained, and network deployment and centralized operation and maintenance can be quickly realized through the operation and maintenance platform.

### ■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR, SYS, Link, L/A.
- ◇ Low power consumption, No fan, aluminum shell, excellent heat dissipation to ensure

the stable operation of the switch.

## TECHNICAL SPECIFICATION

Model	ONV-IPS53064FM
<b>Interface Characteristics</b>	
Fixed Port	4*10/100/1000Base-T RJ45 ports (Data) 2*100/1000Base-X uplink SFP ports (Data) 2 groups of V+, V- redundant DC power port (5P phoenix terminal)
Ethernet Port	Port 1-4 support 10/100/1000Base-T auto-sensing, full/ half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meters) 100BASE-TX: Cat5 or later UTP(≤100 meters) 1000BASE-T: Cat5e or later UTP(≤100 meters)
SFP Slot Port	Gigabit SFP optical fiber interface, default no included optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable/Distance	Multi-mode: 850nm/ 0-500m, Single-mode: 1310nm/ 0-40km, 1550nm / 0-120km.
<b>Chip Parameter</b>	
Network Management Type	L2 (Web management, platform management)
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3x
Forwarding Mode	Store and Forward(Full wire-speed)
Switching Capacity	12Gbps
Forwarding Rate@64byte	8.93Mpps
MAC	2K

Buffer Memory	2M
Jumbo Frame	9.2K
LED Indicator	Fiber port: L/A (Green), Network: Link (Yellow), Power/ System: SYS (Green)
Reset Switch	Press and hold for 6 seconds and release to restore the factory default settings, short press 2 times (1 second interval) to switch to the unmanaged state
<b>Power Supply</b>	
Total Power/ Input Voltage	5W/ 12-57VDC
Power Consumption	Standby<4W, Full load<6W
Interface	5 Pin industrial Phoenix terminal, support anti-reverse protection.
Power Supply	No, optional 12V/ 12W or 24V/ 24W industrial power supply
<b>Physical Parameter</b>	
Operation TEMP / Humidity	-40°C~+75°C, 5%~90% RH Non condensing
Storage TEMP / Humidity	-40°C~+85°C, 5%~95% RH Non condensing
Dimension (L*W*H)	119*100*30mm
Net /Gross Weight	<0.35kg / <0.5kg
Installation	Desktop, 35mm DIN rail
<b>Certification &amp; Warranty</b>	
Lightning Protection	Protection level: IP40 Lightning protection: 6KV 8/20us IEC61000-4-3 (RS):10V/m(80~1000MHz) FCC Part 15/ CISPR22 (EN55022): Class B IEC61000-6-2 (Common Industrial Standard)


	IEC61000-4-9 (Pulsed magnet field): 1000A/m IEC61000-4-10 (Damped oscillation): 30A/m 1MHz IEC61000-4-12/18 (Shockwave): CM 2.5kV, DM 1kV IEC61000-4-4 (EFT): Power cable:±4kV, data cable: ±2kV IEC61000-4-16 (Common-mode transmission): 30V, 300V, 1s IEC61000-4-2 (ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-6 (Radio frequency transmission):10V (150kHz~80MHz) IEC61000-4-5 (Surge): Power cable: CM±4kV/DM±2kV, data cable: ±4kV IEC61000-4-8 (Power frequency magnetic field):100A/m, 1000A/m,1s to 3s
Mechanical	IEC60068-2-32 (free fall)
Properties	IEC60068-2-6 (anti vibration), IEC60068-2-27 (anti shock)
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS
Warranty	5 years, lifelong maintenance.

### Network Management Features

Interface	Port status display, Port traffic statistics Port duplex/ negotiation rate configuration EEE Energy-saving and green Ethernet function IEEE802.3x flow control configuration (Full-duplex)
VLAN	Port-based IEEE802.1Q VLAN configuration (4K)
Port Aggregation	Static aggregation
Loop Protection	Loop protection function
Multicast	IGMP Snooping v1/v2, Max 256 multicast groups
Port Mirroring	Bidirectional data mirroring based on port
QoS	Diff-Serv QoS, Priority Mark/ Remark 8*Output queues of each port, 802.1p/ DSCP priority mapping
Security	Broadcast storm control, Port isolation, Port speed limit
DHCP	DHCP Snooping

Management	<p>Mobile APP operation and maintenance management</p> <p>ONV-NMS platform management (Local platform/ Cloud platform)</p> <p>One-key recovery, Cable Diagnose, Web Management (HTTPS)</p>
System	<p>Category 5 Ethernet network cable</p> <p>Web browser: Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later;</p> <p>TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network</p>

## DIMENSION



## ORDERING INFORMATION

Model	Description	Recommended Power Supply
ONV-IPS53064FM	L2 managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 2*100/1000M SFP ports. It can support redundant dual DC power input and DIN rail mounting.	12W/24W

**Note:** Industrial Ethernet switch does not included the SFP optical module and power supply.

## PACKING LIST

Packing List	Content	Qty	Unit
	6-port full gigabit cloud managed industrial switch	1	SET
	User Guide	1	PC
	Warranty Card	1	PC

## OPTICAL MODULE

Product	Model	Description	Unit
1.25G Optical Module	2630-G	Industrial SFP optical module, 1.25G, multi-mode dual fiber 850nm, transmission distance: 550m, LC interface, support DDM function, support hot plug and pull.	PC
	2632-G	Industrial SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2612-T-G	Industrial SFP optical module, 1.25G, single-mode single fiber TX1310nm/ RX1550nm, transmission distance:	PC

		20km, LC interface, support DDM function, support hot plug and pull.	
	2613-R-G	Industrial SFP optical module, 1.25G, single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2612-T-G-SC	Industrial SFP optical module, 1.25G, single-mode single fiber TX1310nm/ RX1550nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.	PC
	2613-R-G-SC	Industrial SFP optical module, 1.25G, single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.	PC
Power Module	2633	1.25G SFP optical module transfers to 10/100/1000M RJ45 port.	PC

## POWER SUPPLY

Product	Model	Description	Unit
12W DIN Rail Industrial Power Supply	GWS-DP12-12	Din Rail 12W single set of output power supply Input Voltage: AC100V~240V 50-60H, 0.5A Output Voltage: DC12V, 1A Operation Temperature: -40°C to +70°C	PC
24W DIN Rail Industrial Power Supply	GWS-DP24-24	Din Rail 24W single set of output power supply Input Voltage: AC100V~240V 50-60H, 0.65A Output Voltage: DC24V, 1.0A Operation Temperature: -40°C to +70°C	PC

## RELATED PRODUCT

Model	Description
ONV-IPS53054FM	L2 managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 1*100/1000M SFP port. It can support redundant dual DC power input and DIN rail mounting.
ONV-IPS53064FGM	L2 managed industrial Ethernet fiber switch with 5*10/100/1000M RJ45 ports and 1*100/1000M SFP port. It can support redundant dual DC power input and DIN rail mounting.
ONV-IPS53008FM	L2 managed industrial Ethernet switch with 8*10/100/1000M RJ45 ports. It can support redundant dual DC power input and DIN rail mounting.
ONV-IPS53108FM	L2 managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 2*100/1000M SFP ports. It can support redundant dual DC power input and DIN rail mounting.

## CONTACT US



**Optical Network Video Technologies (Shenzhen) Co., Ltd.**

Tel: 0086-755-33376606

Fax: 0086-755-33376608

WeChat: ONV-PoE-IoT

Email: onv@onv.com.cn

Skype: onv@onv.com.cn

Website: www.onvcom.com

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen, China

Factory Address: Floor 4-6, Building A, Senyutai Industrial Park, No. 111, Huaning Road

9

+86 ;

Optical Network Video Technologies (Shenzhen)



Xinshi Community, Dalang Street, Longhua District, Shenzhen, China