

Product Datasheet

6-port Gigabit Industrial PoE Switch

(ONV-IPS3064P)



OVERVIEW

The ONV-IPS3064P is a Gigabit industrial PoE switch independently developed by ONV. It has 6*10/100/1000M adaptive RJ45 ports. Ports 1-4 support the IEEE 802.3af/at PoE standard, with single-port PoE power up to 30W. As a PoE power supply device, it can automatically detect and recognize the power-receiving equipment that meets the standard and supply power through the network cable. The network cable can supply power to PoE terminal devices such as wireless APs, IP cameras, and industrial sensors. It also meets the needs of network environments that require a high-density PoE power supply. It is suitable for intelligent transportation, rail transit, the power industry, mining, petroleum, and sea transportation. Industrial scenes such as metallurgy, green energy, and construction form a cost-effective, stable, and reliable communication network. Plug-and-play and easy to use.

FEATURE

■ Gigabit access

- ◇ Support non-blocking wire-speed forwarding.

- ◇ Support full-duplex based on IEEE 802.3x and half-duplex based on Backpressure.
- ◇ Support Gigabit PoE port and uplink RJ45 port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

■ Smart PoE power supply

- ◇ Complies with IEEE 802.3 af/at PoE standard, automatically identifies PoE devices for power supply, and does not damage non-PoE devices.
- ◇ 4*10/100/1000Base-T RJ45 ports can support PoE power supply to meet the needs of PoE power supply in various scenarios in the industrial field.

■ Stable and reliable

- ◇ CE, FCC, RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicators for PWR, Link, and PoE.
- ◇ Low power consumption, aluminum alloy housing, and excellent heat dissipation to ensure the stable operation of the switch.


TECHNICAL SPECIFICATION

Model	ONV-IPS3064P
Interface Characteristics	
Fixed Port	1*DC5521 power socket 2*10/100/1000Base-T uplink RJ45 ports (Data) 4*10/100/1000Base-T PoE ports (Data/ Power) 1 V+, V- (3P Phoenix terminal) DC power interface Dual power interfaces support reverse-connection protection
Ethernet Port	Ports 1-6 support 10/100/1000Base-T auto-sensing, full/ half duplex MDI/ MDI-X self-adaptation
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meters) 100BASE-TX: Cat5 or later UTP (≤100 meters)

	1000BASE-T: Cat5e or later UTP (≤100 meters)
Chip Parameter	
Network Protocol	IEEE 802.3 10BASE-T, IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3x
Forwarding Mode	Store and forward (Full wire speed)
Switching Capacity	12Gbps (non-blocking)
Forwarding Rate@64byte	8.93Mpps
MAC	2K
Buffer Memory	2M
Jumbo Frame	9.2K
LED Indicator	Power: PWR (Green), Network: Link G1-G6 (Green), PoE: PoE G1-G4 (Red)
PoE& Power Supply	
PoE Port	Port 1-4
Power Supply Pin	1/2(+) 3/6(-)
Max Power Per Port	30W, IEEE 802.3 af/at
Power Consumption	Standby<3W, Full load af<60W, at<120W
Operation Voltage	DC44-56V
Power Supply	No, optional 48V/60W and 48V/120W industrial power supply
Physical Parameter	
Operation Temp/ Humidity	-40~+75°C, 5%~90% RH non-condensing
Storage Temp/ Humidity	-40~+85°C, 5%~95% RH non-condensing
Dimension	98*88*30mm
Net /Gross Weight	0.25kg/ 0.35kg
Installation	Desktop, 35mm DIN Rail
Certification& Warranty	
Lightning Protection	IEC61000-4-3 (RS):10V/m (80~1000MHz) FCC Part 15/CISPR22 (EN55022): Class A IEC61000-6-2 (Common Industrial Standard)

	IEC61000-4-9 (Pulsed magnetic field): 1000A/m IEC61000-4-10 (Damped oscillation): 30A/m 1MHz IEC61000-4-12/18 (Shockwave): CM2.5kV, DM1kV Protection level: IP30, Lightning protection: 6KV 8/20us IEC61000-4-4(EFT): Power cable: ± 4 kV, data cable: ± 2 kV IEC61000-4-16 (Common-mode transmission): 30V, 300V, 1s IEC61000-4-2 (ESD): ± 8kV contact discharge, ± 15kV air discharge IEC61000-4-6 (Radio frequency transmission): 10V(150 kHz- 80 MHz) IEC61000-4-8 (Power frequency magnetic field): 100A/m, 1000A/m, 1s-3s IEC61000-4-5 (Surge): Power cable: CM± 4kV/ DM± 2kV, data cable: ± 4kV
Mechanical Properties	IEC 60068-2-6 (Anti vibration), IEC 60068-2-32 (Free fall), IEC 60068-2-27 (Anti shock)
Certification	CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class A, RoHS
Warranty	5 years, lifelong maintenance.

DIMENSION



APPLICATION



Plug and play



Wide temperature range




DIN Rail installation



PoE: DC44-56V
(Dual power supply)

Power



Server




NVR



Network users



Core Switch



PoE IP Phone



PoE IP Camera



Access Point

ORDERING INFORMATION

Model	Description	Recommended Power Supply
ONV-IPS3064P	Industrial PoE switch with 6*10/100/1000M RJ45 ports. Ports 1-4 support the IEEE 802.3 af/at PoE standard. It supports dual DC power input and DIN rail mounting.	60W/120W

Note: The power supply is not included and needs to be purchased.

PACKING LIST

Packing List	Content	Qty	Unit
	6-port Gigabit industrial PoE switch	1	PC
	User Guide	1	PC
	Warranty Card and Certificate of Conformity	1	PC

POWER SUPPLY

Product	Model	Description	Unit
65W Desktop power adapter	GWS-AP65-52	Desktop 65W single-set output power adapter Input voltage: AC100V~240V 50-60Hz, 1.1A Output voltage: DC52V, 1.25A Operation temperature: -20℃ to +65℃	PC
110W Desktop power adapter	GWS-AP110-52	Desktop 110W single-set output power adapter Input voltage: AC100V~240V 50-60Hz, 2.0A Output voltage: DC52V, 2.15A Operation temperature: -20℃ to +65℃	PC
60W DIN Rail industrial power supply	GWS-DP60-48	DIN Rail 60W single-set output power supply Input voltage: AC100V~240V 50-60Hz, 1.6A Output voltage: DC48V, 1.25A Operation temperature: -40℃ to +70℃	PC
120W DIN Rail industrial power supply	GWS-DP120-48	DIN Rail 120W single-set output power supply Input voltage: AC100V~240V 50-60Hz, 2.3A Output voltage: DC48V, 2.5A Operation temperature: -40℃ to +70℃	PC

CONTACT US



Optical Network Video Technologies (Shenzhen) Co., Ltd.



Tel: 0086-755-33376606

Fax: 0086-755-33376608

Email: onv@onv.com.cn

Skype: [onv@onv.com.cn](https://www.skype.com/people/onv@onv.com.cn)

WeChat ID: ONV-PoE-IoT

Website: www.onvcom.com, www.onvswitch.com

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen

Factory Address: Building B3, Galaxy Artificial Intelligence Industrial Park, No. 333,

Zhongkai 6th Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou

